TECHNICAL SPECIFICATIONS

Ticket Printer – Z800 / Z800L

Ticket Printer 80mm

USB / USB+LAN



Features

* Front or Top receipt Exit.
* Long lasting auto-cutter up to 1.5million cuts.
* Built-in Power adapter.
* Support 8 kinds of different paper width (Option).
* Support wall mounting.

Model	POSLUX Z800 / Z800L
Print Method	Direct Thermal
Print Speed	230 mm/s
Resolution	576 dots/line or 572dots/line
Printing Width	72 mm
Paper separator(option)	48mm/52mm/56mm/64mm/68mm/76mm/80mm
Interface	USB / USB+LAN
Input buffer	64 kbyte
NV Flash	256 kbytes
Font A	12x24
Font B	9x17
User-defined	Support
Barcode	**1D** UPC-A/UPC-E/JAN13（EAN13）/JAN8（EAN8）/CODE39/ITF/CODABAR/CODE93/CODE128 **2D** QR CODE
Sensors	Paper out, cover open, cutter jam, paper jam
Input	AC 100V-240V 50/60HZ
Output	DC 24V/2.5A
Paper Type	Thermal Receipt Paper
Paper Width(option)	48mm/52mm/56mm/64mm/68mm/76mm/80mm
Paper Thickness	0.06~0.08mm
Roll Dia	Max. Ø 83 mm
Paper Load	Easy paper loading
Paper Cut	Manual tear & Auto-cutter
Working Condition	0°C~45°C, 10%~80%RH
Storage Condition	-10°C-60°C,10%~90%RH
Dimensions	191(D)x146(W)x12.9(H)mm
Net weight	1.94 kg
Printing head	150 KM
cutter	1.5 million
Accessories	Data cable, power code,paper roller, CD, manual,paper separator(option)
Emulation	ESC/POS
Driver	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS
SDK	Android, IOS

RoHS Compliant